

Installation

25. Reassemble the lower steering column shroud cover, the upper steering column shroud cover, the steering column tilt wheel release lever, lower dashboard panel, and A pillar trim.



26. Effect of installation



Installation Manual

VS012-GM-SLV/SRA

12.1 inch Audio / Video / Navigation Receiver
For The Silverado And Sierra (2014 - 2018)

安 装 注 意 事 项

一、主机安装要求

1. 装机前先启动发动机，检查汽车仪表功能显示、车内按键是否正常，车内外表面有无刮花现象，如有问题，及时向客户反映。
2. 安装过程中注意拆下的汽车配件要放好，避免刮花车内仪表台和车内饰。接线时留下的杂物及时处理，不要留在车内，接头处一定要做好绝缘，防止短路。
3. 布线要合理。车内安装空间较小，所以尽量减少不必要的线材，减少占用空间，使主机易于安装。

二、导航天线安装要求

1. GPS接收天线建议放置在车顶外，接收信号较强，也可置于车内前方玻璃下方的仪表台上，用3M双面胶做好固定。
2. 安装GPS接收天线时，须水平放置，正面朝上，对着天空，这样较好接收卫星信号。如果车子装有防爆膜，将会降低GPS信号的接收，可在GPS天线上方位置割去一小块防爆膜，降低对接收信号的影响。
3. 安装完成后，对导航进行调试。在主界面中，点击“导航”即可以直接进入导航系统。

三、安装工具要求

1. 十字螺丝刀一把
2. 塑胶撬柄两把
3. 3M胶或双面胶一卷
4. 电工胶布一卷
5. 文具剪刀一把



Installation

1. Use a flat bladed plastic trim tool to release the retainer clips securing the accessory bezel to the instrument panel assembly.



2. There are 10 retainer clips on the accessory bezel.



3. You can use hands to pull the accessory bezel away from the instrument panel assembly after you release several retainer clips. Disconnect the electrical connections on the accessory bezel, if equipped.



4. Remove the four 7 mm retaining screws securing the Radio Control Assembly.



5. Remove the four 7 mm retaining screws securing the Radio Control Assembly.



6. Pull the Radio Control Assembly away from the instrument panel assembly to release retainer clips at the back.



7. Disconnect the electrical connections at the back of the Radio Control Assembly.



8. Remove the two 7 mm retaining screws securing the Disc Player.



9. Pull out the Disc Player and Disconnect the electrical connectors at the back.



10. Route the A/C harness from below the Disc Player to the side of the Disc player, and connect the extension harness. (Before)



11. (After)



12. Put back the Disc Player, connect the electrical connector, and tighten the two 7 mm retaining screws.



Installation

13. (Skip to step 17 if you don't have previous/next track steering wheel control) Remove the steering column tilt wheel release lever by pulling it outward.



14. Use a flat bladed plastic trim tool to release the tabs securing the upper steering column shroud cover to the lower steering column shroud cover, and remove the upper steering column shroud cover.



15. Pull the lower dash panel away from the dash to release the retainer clips, and remove the lower steering column shroud cover.



16. Route the steering wheel control adapter T-harness from above the Disc Player to the steering wheel column through behind the dash. Disconnect the steering wheel control connectors and connect the T-harness between them.



17. Disconnect the electrical power connector for the radio module and connect the T-harness between them.



18. Route the GPS antenna from above the Disc Player to a suitable place (inside windshield, on top of dashboard, or A pillar), and secure it with double sided tape.



19. (Optional) Route the external mic from above the Disc Player to driver-side headliner



20. Route the USB harness from above the Disc Player to glove box or another location convenient for you.



21. Transfer the ten metal clips and seat heater switches, if equipped, from the instrument panel accessory bezel to the new head unit.



22. Connect the electrical connectors at the back of the new head unit, including OEM screen connector, OEM mini USB connector, A/C connector, audio harness connector, GPS antenna connector, external mic connector, USB harness connector, seat heater switch connector, if equipped.



23. Align the retainer clips and push the new head unit towards the instrument panel assembly to engage the retainer clips to secure the new head unit.



24. Test out the features. If previous/next track steering wheel control doesn't work, try the other two pin connector on the steering wheel adapter harness.

